


TRAPPED GULLY PIT WITH SAND BAFFLE  
BASE SHOWN FOR DRY CONDITIONS  
(BASE IS MORE THAN 500mm ABOVE AMGL)  
NTS

ROAD GULLY PIT AND GRATE  
NTS

COMBINATION SIDE ENTRY PIT AND GRATE  
FOR USE AT LOW POINTS.

- NOTES
- CONCRETE TO BE 20mm NOMINAL AGGREGATE AND HAVE A MINIMUM COMPRESSIVE STRENGTH AT 28 DAYS OF:
    - 20MPa FOR INSITU BASE
    - 40MPa FOR PRECAST UNITS
  - ALL BASES TO BE BEDDED ON FIRM NATURAL OR COMPACTED SAND
  - PIPE JOINTS WITHIN 1.0m OF PIT TO BE SEALED
  - SUBGRADE TO BASE TO BE COMPACTED TO 95% M.M.D.D. PRIOR TO PLACING OF BASE
  - BACKFILL SURROUNDING PIT TO BE TO 95% M.M.D.D.
  - MORTAR TO BE 3 : 1 SAND : CEMENT MIXTURE

No.	Revision	Chk'd	App'd	Date
H	UPDATED PIPES DETAILS WITHIN PIT			08/09/23
G				15/03/23
F				13/10/21
E				12/02/21
D				3/12/20



CITY OF COCKBURN  
9 COLEVILLE CRESCENT,  
SPEARWOOD WA 6163  
PHONE: (08) 9411 3444  
STANDARD DETAILS

DESIGNED		APPROVED		SCALE	JOB No
NS	NS	NS	NS	AS SHOWN	
DRAWN	NS	DATE		DWG No	SHEET No
CHECKED				2423B03	10
					REV H